

# 珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电		能量 Energy (2ms)	最大峰值电流		最大限值电压		电容量 (参考值) Capacitance (Reference)(1kHz)
	Vari toVoltage	压			Max. Peak Current (8/20; s) (A)		Max. Clamping Voltage		
	V <sub>1mA</sub> (V)	AC <sub>rms</sub>	DC	(J)	1time	2time	Vc(V)	I <sub>p</sub> (A)	pF
MYL5A22K201	200(180~220)	130	170	200	20000	15000	340	150	5800
MYL5A22K221	220(198~242)	140	180	200	20000	15000	360	150	5450
MYL5A22K241	240(216~264)	150	200	200	20000	15000	395	150	4900
MYL5A22K271	270(243~297)	175	225	240	20000	15000	455	150	4700
MYL5A22K301	300(270~330)	190	245	270	20000	15000	495	150	4300
MYL5A22K331	330(297~363)	215	275	300	20000	15000	540	150	3720
MYL5A22K361	360(324~396)	230	300	300	20000	15000	595	150	3350
MYL5A22K391	390(351~429)	250	320	330	20000	15000	650	150	3000
MYL5A22K431	430(387~473)	275	350	360	20000	15000	710	150	2800
MYL5A22K471	470(423~517)	300	385	360	20000	15000	775	150	2600
MYL5A22K511	510 (459~561)	320	415	390	20000	15000	855	150	2400
MYL5A22K561	560 (504~616)	350	455	390	20000	15000	945	150	2200
MYL5A22K621	620 (558~682)	380	505	390	20000	15000	1025	150	2000
MYL5A22K681	680 (612~748)	420	560	400	20000	15000	1120	150	1800
MYL5A22K751	750(675~825)	460	615	440	20000	15000	1240	150	1600
MYL5A22K821	820(738~902)	510	670	500	20000	15000	1355	150	1500
MYL5A22K911	910(819~1001)	550	745	550	20000	15000	1500	150	1350
MYL5A22K102	1000(900~1100)	625	825	600	20000	15000	1650	150	1150
MYL5A22K112	1100(990~1210)	680	895	650	20000	15000	1815	150	1000
MYL5A22K122	1200(1080~1320)	705	987	700	50000	15000	1980	150	700

# 珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电		能量	最大峰值电流		最大限值电压		电容量 (参考值)
	Vari toVoltage	压		Energy	Max. Peak		Max. Clamping		Capacitance
	$V_{1mA}$ (V)	Max. Allowable	Vol tage(V)	(2ms)	Current(8/20; s)	(A)	Vol tage		(Reference)(1kHz)
		AC <sub>rms</sub>	DC	(J)	1time	2time	Vc(V)	Ip(A)	pF
MYL5B34K201	200(180~220)	130	170	270	30000	20000	340	200	6900
MYL5B34K341	220(198~242)	140	180	270	30000	20000	360	200	6300
MYL5B34K241	240(216~264)	150	200	300	30000	20000	395	200	5400
MYL5B34K271	270(243~297)	175	225	300	30000	20000	455	200	4900
MYL5B34K301	300(270~330)	190	245	330	30000	20000	495	200	4200
MYL5B34K331	330(297~363)	215	275	350	30000	20000	540	200	3950
MYL5B34K361	360(324~396)	230	300	350	40000	25000	595	200	3700
MYL5B34K391	390(351~429)	250	320	370	40000	25000	650	200	3400
MYL5B34K431	430(387~473)	275	350	400	40000	25000	710	200	3200
MYL5B34K471	470(423~517)	300	385	430	40000	25000	775	200	3000
MYL5B34K511	510 (459~561)	320	415	460	40000	25000	855	200	2800
MYL5B34K561	560 (504~616)	350	455	500	40000	25000	945	200	2600
MYL5B34K621	620 (558~682)	380	505	550	40000	25000	1025	200	2450
MYL5B34K681	680 (612~748)	420	560	600	40000	25000	1120	200	2200
MYL5B34K751	750(675~825)	460	615	650	40000	25000	1240	200	1700
MYL5B34K821	820(738~902)	510	670	700	40000	25000	1355	200	1400
MYL5B34K911	910(819~1001)	550	745	750	40000	25000	1500	200	1300
MYL5B34K102	1000(900~1100)	625	825	800	40000	25000	1650	200	1150
MYL5B34K112	1100(990~1210)	680	895	900	40000	25000	1815	200	850
MYL5B34K134	1200(1080~1320)	705	987	1050	40000	25000	1980	200	740

# 珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电		能量 Energy (2ms)	最大峰值电流		最大限值电压		电容量 (参考值) Capacitance (Reference)(1kHz)
	Vari toVoltage	压			Max. Peak Current(8/20; s)		Max. Clamping Voltage		
	V <sub>1mA</sub> (V)	AC <sub>rms</sub>	DC	(J)	1time	2time	Vc(V)	I <sub>p</sub> (A)	pF
MYL5B38K201	200(180~220)	130	170	310	40000	25000	340	400	8100
MYL5B38K381	220(198~242)	140	180	330	40000	25000	360	400	7800
MYL5B38K241	240(216~264)	150	200	360	40000	25000	395	400	7400
MYL5B38K271	270(243~297)	175	225	380	40000	25000	455	400	6750
MYL5B38K301	300(270~330)	190	245	400	40000	25000	495	400	5900
MYL5B38K331	330(297~363)	215	275	430	40000	25000	540	400	5300
MYL5B38K361	360(324~396)	230	300	460	50000	30000	595	400	4700
MYL5B38K391	390(351~429)	250	320	490	50000	30000	650	400	4300
MYL5B38K431	430(387~473)	275	350	550	50000	30000	710	400	3900
MYL5B38K471	470(423~517)	300	385	590	50000	30000	775	400	3500
MYL5B38K511	510 (459~561)	320	415	640	50000	30000	855	400	3200
MYL5B38K561	560 (504~616)	350	455	720	50000	30000	945	400	2800
MYL5B38K621	620 (558~682)	380	505	800	50000	30000	1025	400	2700
MYL5B38K681	680 (612~748)	420	560	830	50000	30000	1120	400	2600
MYL5B38K751	750(675~825)	460	615	850	50000	30000	1240	400	2430
MYL5B38K821	820(738~902)	510	670	920	50000	30000	1355	400	2150
MYL5B38K911	910(819~1001)	550	745	960	50000	30000	1500	400	1900
MYL5B38K102	1000(900~1100)	625	825	1020	50000	30000	1650	400	1750
MYL5B38K112	1100(990~1210)	680	895	1100	50000	30000	1815	400	1530
MYL5B38K122	2000(1080~1320)	705	987	1200	50000	30000	1980	400	1200

地址:珠海香洲区香华路288号8-2-302 邮编:519000 电话:0756-2266730 传真:0756-3362716