

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电 压		能量	最大峰值电流		最大峰值电压		静态功率	电容量(参考值)
	Vari toVoltage	Max. Allowable Voltage(V)		Energy (2ms)	Max. Peak Current (8/20, s) (A)		Max. Clamping Voltage		Rared Power	Capaci tance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	Ip(A)	(W)	pF
MYL1A40K470	47(42-52)	30	38	70	15000	10000	93	100	0.3	30000
MYL1A40K560	56(50-62)	35	45	80	15000	10000	110	100	0.3	27000
MYL1A40K680	68(61-75)	40	56	90	15000	10000	115	100	0.3	25000
MYL1A40K820	82(74-90)	50	65	100	15000	10000	135	100	0.3	20000
MYL1A40K101	100(90-110)	60	85	110	15000	10000	165	100	0.3	18000
MYL1A40K121	120(108-130)	75	100	120	15000	10000	200	100	0.3	16000
MYL1A40K151	150(135-165)	95	125	130	15000	10000	250	100	1.2	13000
MYL1A40K181	180(162-198)	115	150	140	15000	10000	300	100	1.2	10000
MYL1A40K201	200(180-220)	130	170	270	30000	20000	340	250	1.2	6200
MYL1A40K221	220(198-242)	140	180	270	30000	20000	360	250	1.2	5500
MYL1A40K241	240(216-264)	150	200	300	30000	20000	395	250	1.2	5100
MYL1A40K271	270(243-297)	175	225	300	30000	20000	455	250	1.2	4800
MYL1A40K301	300(270-330)	190	245	330	30000	20000	495	250	1.2	4300
MYL1A40K331	330(297-363)	215	275	350	30000	20000	540	250	1.2	4000
MYL1A40K361	360(324-396)	230	300	350	40000	25000	595	250	1.2	3800
MYL1A40K391	390(351-429)	250	320	370	40000	25000	650	250	1.2	3400
MYL1A40K431	430(387-473)	275	350	400	40000	25000	710	250	1.2	3100
MYL1A40K471	470(423-5170)	300	385	430	40000	25000	775	250	1.2	2800
MYL1A40K511	510(459-561)	320	415	460	40000	25000	855	250	1.2	2600
MYL1A40K561	560(504-616)	350	455	500	40000	25000	945	250	1.2	2400
MYL1A40K621	620(558-682)	380	505	550	40000	25000	1025	250	1.2	2100
MYL1A40K681	680(612-748)	420	560	600	40000	25000	1120	250	1.2	1900
MYL1A40K751	750(675-825)	460	615	650	40000	25000	1240	250	1.2	1700
MYL1A40K821	820(738-902)	510	670	700	40000	25000	1355	250	1.2	1600
MYL1A40K911	910(819-1001)	550	745	750	40000	25000	1500	250	1.2	1500
MYL1A40K102	1000(900-1100)	625	825	800	40000	25000	1650	250	1.2	1350
MYL1A40K112	1100(990-1210)	680	895	900	40000	25000	1815	250	1.2	1200
MYL1A40K122	1200(1080-1320)	705	970	1050	40000	25000	1980	250	1.2	1050

地址:珠海香洲区香华路288号8-2-302 邮编:519000 电话:0756-2266730 传真:0756-3362716

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电		能量 Energy (2ms)	最大峰值电流		最大峰值电压		静态功率 Rated Power	电容量(参考值) Capacitance (Reference)(1kHz)
	Vari toVoltage	压			Max. Peak Current (8/20, s) (A)		Max. Clamping Voltage			
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	Ip(A)	(W)	pF
MYL1A40K470	47(42-52)	30	38	70	15000	10000	93	100	0.3	30000
MYL1A40K560	56(50-62)	35	45	80	15000	10000	110	100	0.3	27000
MYL1A40K680	68(61-75)	40	56	90	15000	10000	115	100	0.3	25000
MYL1A40K820	82(74-90)	50	65	100	15000	10000	135	100	0.3	20000
MYL1A40K101	100(90-110)	60	85	110	15000	10000	165	100	0.3	18000
MYL1A40K121	120(108-130)	75	100	120	15000	10000	200	100	0.3	16000
MYL1A40K151	150(135-165)	95	125	130	15000	10000	250	100	1.2	13000
MYL1A40K181	180(162-198)	115	150	140	15000	10000	300	100	1.2	10000
MYL1A40K201	200(180-220)	130	170	270	30000	20000	340	250	1.2	6200
MYL1A40K221	220(198-242)	140	180	270	30000	20000	360	250	1.2	5500
MYL1A40K241	240(216-264)	150	200	300	30000	20000	395	250	1.2	5100
MYL1A40K271	270(243-297)	175	225	300	30000	20000	455	250	1.2	4800
MYL1A40K301	300(270-330)	190	245	330	30000	20000	495	250	1.2	4300
MYL1A40K331	330(297-363)	215	275	350	30000	20000	540	250	1.2	4000
MYL1A40K361	360(324-396)	230	300	350	40000	25000	595	250	1.2	3800
MYL1A40K391	390(351-429)	250	320	370	40000	25000	650	250	1.2	3400
MYL1A40K431	430(387-473)	275	350	400	40000	25000	710	250	1.2	3100
MYL1A40K471	470(423-517)	300	385	430	40000	25000	775	250	1.2	2800
MYL1A40K511	510(459-561)	320	415	460	40000	25000	855	250	1.2	2600
MYL1A40K561	560(504-616)	350	455	500	40000	25000	945	250	1.2	2400
MYL1A40K621	620(558-682)	380	505	550	40000	25000	1025	250	1.2	2100
MYL1A40K681	680(612-748)	420	560	600	40000	25000	1120	250	1.2	1900
MYL1A40K751	750(675-825)	460	615	650	40000	25000	1240	250	1.2	1700
MYL1A40K821	820(738-902)	510	670	700	40000	25000	1355	250	1.2	1600
MYL1A40K911	910(819-1001)	550	745	750	40000	25000	1500	250	1.2	1500
MYL1A40K102	1000(900-1100)	625	825	800	40000	25000	1650	250	1.2	1350
MYL1A40K112	1100(990-1210)	680	895	900	40000	25000	1815	250	1.2	1200
MYL1A40K122	1200(1080-1320)	705	970	1050	40000	25000	1980	250	1.2	1050

地址:珠海香洲区香华路288号8-2-302 邮编:519000 电话:0756-2266730 传真:0756-3362716

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电 压		能量	最大峰值电流		最大峰值电压		静态功率	电容量 (参考值)
	Vari toVoltage	Max. Allowable Voltage (V)		Energy (2ms)	Max. Peak Current (8/20; s) (A)		Max. Clamping Voltage		Rared Power	Capaci tance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	I _p (A)	(W)	pF
MYL1A50K201	200(180-220)	130	170	310	40000	25000	340	300	1.4	12000
MYL1A50K221	220(198-242)	140	180	330	40000	25000	360	300	1.4	10500
MYL1A50K241	240(216-264)	150	200	360	40000	25000	395	300	1.4	9000
MYL1A50K271	270(243-297)	175	225	380	40000	25000	455	300	1.4	7500
MYL1A50K301	300(270-330)	190	245	400	40000	25000	495	300	1.4	6300
MYL1A50K331	330(297-363)	215	275	430	40000	25000	540	300	1.4	5200
MYL1A50K361	360(324-396)	230	300	460	50000	30000	595	300	1.4	4500
MYL1A50K391	390(351-429)	250	320	490	50000	30000	650	300	1.4	4100
MYL1A50K431	430(387-473)	275	350	550	50000	30000	710	300	1.4	3800
MYL1A50K471	470(423-517)	300	385	590	50000	30000	775	300	1.4	3400
MYL1A50K511	510(459-561)	320	415	640	50000	30000	855	300	1.4	3100
MYL1A50K561	560(504-616)	350	455	720	50000	30000	945	300	1.4	2900
MYL1A50K621	620(558-682)	380	505	800	50000	30000	1025	300	1.4	2700
MYL1A50K681	680(612-748)	420	560	830	50000	30000	1120	300	1.4	2550
MYL1A50K751	750(675-825)	460	615	850	50000	30000	1240	300	1.4	2400
MYL1A50K821	820(738-902)	510	670	920	50000	30000	1355	300	1.4	2200
MYL1A50K911	910(819-1001)	550	745	960	50000	30000	1500	300	1.4	2100
MYL1A50K102	1000(900-1100)	625	825	1020	50000	30000	1650	300	1.4	1900
MYL1A50K112	1100(990-1210)	680	895	1100	50000	30000	1815	300	1.4	1750
MYL1A50K122	1200(1080-1320)	705	970	1200	50000	30000	1980	300	1.4	1600

珠海华星龙企业有限公司

型号 Model NO.	压敏电压 Varistor Voltage	最大容许回路电压 Max. Allowable Voltage(V)		能量 Energy (2ms)	最大峰值电流 Max. Peak Current (8/20; s) (A)		最大峰值电压 Max. Clamping Voltage		静态功率 Rated Power	电容量 (参考值) Capacitance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	I _p (A)	(W)	pF
MYL1A60K201	200(180-220)	130	170	450	50000	30000	340	350	1.6	17000
MYL1A60K221	220(198-242)	140	180	450	50000	30000	360	350	1.6	15000
MYL1A60K241	240(216-264)	150	200	530	50000	30000	395	350	1.6	14000
MYL1A60K271	270(243-297)	175	225	550	50000	30000	455	350	1.6	12000
MYL1A60K301	300(270-330)	190	245	600	50000	30000	495	350	1.6	10000
MYL1A60K331	330(297-363)	215	275	650	50000	30000	540	350	1.6	9600
MYL1A60K361	360(324-396)	230	300	700	70000	45000	595	350	1.6	8900
MYL1A60K391	390(351-429)	250	320	880	70000	45000	650	350	1.6	7700
MYL1A60K431	430(387-473)	275	365	950	70000	45000	710	350	1.6	6900
MYL1A60K471	470(423-517)	300	385	1000	70000	45000	775	350	1.6	6500
MYL1A60K511	510(459-561)	320	415	1100	70000	45000	855	350	1.6	6000
MYL1A60K561	560(504-616)	350	455	1200	70000	45000	945	350	1.6	5500
MYL1A60K621	620(558-682)	380	505	1300	70000	45000	1025	350	1.6	5100
MYL1A60K681	680(612-748)	420	560	1500	70000	45000	1120	350	1.6	4500
MYL1A60K751	750(675-825)	460	615	1600	70000	45000	1240	350	1.6	4300
MYL1A60K821	820(738-902)	510	670	1800	70000	45000	1355	350	1.6	3800
MYL1A60K911	910(819-1001)	550	745	2200	70000	45000	1500	350	1.6	3600
MYL1A60K102	1000(900-1100)	625	825	220	70000	45000	1650	350	1.6	3100
MYL1A60K112	1100(990-1210)	680	895	2350	70000	45000	1815	350	1.6	2800
MYL1A60K122	2000(1080-1320)	705	987	2600	70000	45000	1980	350	1.6	2500

地址:珠海香洲区香华路288号8-2-302 邮编:519000 电话:0756-2266730 传真:0756-3362716