

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电压		能量	最大峰值电流		最大峰值电压		静态 功率	电容量 (参考值)
	Vari toVoltage	Max. Allowable Voltage(V)		Energy (2ms)	Max. Peak Current (8/20; s) (A)		Max. Clamping Voltage		Rared Power	Capacitance (Reference) (1KHz)
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	Ip(A)	(W)	pF
MYL2A25K470	47(42-52)	30	38	35	5000	3000	93	20	0.2	15000
MYL2A25K560	56(50-62)	35	45	40	5000	3000	110	20	0.2	13000
MYL2A25K680	68(61-75)	40	56	45	5000	3000	115	20	0.2	10000
MYL2A25K820	82(74-90)	50	65	50	5000	3000	135	20	0.2	7000
MYL2A25K101	100(90-110)	60	85	55	5000	3000	165	20	0.2	6000
MYL2A25K121	120(108-130)	75	100	60	5000	3000	200	20	0.2	5000
MYL2A25K151	150(135-165)	95	125	75	5000	3000	250	20	0.2	4000
MYL2A25K181	180(162-198)	115	150	85	5000	3000	300	20	0.2	2400
MYL2A25K201	200(180-220)	130	170	100	10000	5000	340	150	0.5	2200
MYL2A25K221	220(198-242)	140	180	100	10000	5000	360	150	0.5	2000
MYL2A25K241	240(216-264)	150	200	120	10000	5000	395	150	0.5	1800
MYL2A25K271	270(243-297)	175	225	130	10000	5000	455	150	0.5	1600
MYL2A25K301	300(270-330)	190	245	160	10000	5000	495	150	0.5	1500
MYL2A25K331	330(297-363)	215	275	160	10000	5000	540	150	0.5	1400
MYL2A25K361	360(324-396)	230	300	180	10000	5000	595	150	0.5	1200
MYL2A25K391	390(351-429)	250	320	200	10000	5000	650	150	0.5	1000
MYL2A25K431	430(387-473)	275	350	220	10000	5000	710	150	0.5	900
MYL2A25K471	470(423-517)	300	385	250	10000	5000	775	150	0.5	900
MYL2A25K511	510(459-561)	320	415	270	10000	5000	855	150	0.5	800
MYL2A25K561	560(504-616)	350	455	270	10000	5000	945	150	0.5	700
MYL2A25K621	620(558-682)	380	505	270	10000	5000	1025	150	0.5	500
MYL2A25K681	680(612-748)	420	560	270	10000	5000	1120	150	0.5	460
MYL2A25K751	750(675-825)	460	615	300	10000	5000	1240	150	0.5	430
MYL2A25K821	820(738-902)	510	670	325	10000	5000	1355	150	0.5	410
MYL2A25K911	910(819-1001)	550	745	360	10000	5000	1500	150	0.5	360
MYL2A25K102	1000(900-1100)	625	825	400	10000	5000	1650	150	0.5	330
MYL2A25K112	1100(990-1210)	680	895	440	10000	5000	1815	150	0.5	310
MYL2A25K122	1200(1080-1320)	705	970	410	10000	5000	1980	150	0.5	270

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电压		能量	最大峰值电流		最大峰值电压		静态	电容量
	Vari toVoltage	Max. Allowable Voltage(V)		Energy (2ms)	Max. Peak Current(8/20, s) (A)		Max. Clamping Voltage		功率 Rared Power	Capacitance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	I _p (A)	(W)	pF
MYL2A32K470	47(42-52)	30	38	45	8000	5000	93	40	0.25	25000
MYL2A32K560	56(50-62)	35	45	50	8000	5000	110	40	0.25	23000
MYL2A32K680	68(61-75)	40	56	55	8000	5000	115	40	0.25	18000
MYL2A32K820	82(74-90)	50	65	62	8000	5000	135	40	0.25	15000
MYL2A32K101	100(90-110)	60	85	70	8000	5000	165	40	0.25	13000
MYL2A32K121	120(108-130)	75	100	80	8000	5000	200	40	0.25	10000
MYL2A32K151	150(135-165)	95	125	90	8000	5000	250	40	0.25	8000
MYL2A32K181	180(162-198)	115	150	100	8000	5000	300	40	0.25	7000
MYL2A32K201	200(180-220)	130	170	200	15000	10000	340	200	1.0	4600
MYL2A32K221	220(198-242)	140	180	200	15000	10000	360	200	1.0	4200
MYL2A32K241	240(216-264)	150	200	220	15000	10000	395	200	1.0	3800
MYL2A32K271	270(243-297)	175	225	240	15000	10000	455	200	1.0	3400
MYL2A32K301	300(270-330)	190	245	270	15000	10000	495	200	1.0	3200
MYL2A32K331	330(297-363)	215	275	300	15000	10000	540	200	1.0	2700
MYL2A32K361	360(324-396)	230	300	300	15000	10000	595	200	1.0	2400
MYL2A32K391	390(351-429)	250	320	330	15000	10000	650	200	1.0	2300
MYL2A32K431	430(387-473)	275	350	360	15000	10000	710	200	1.0	2200
MYL2A32K471	470(423-517)	300	385	360	15000	10000	775	200	1.0	2100
MYL2A32K511	510(459-561)	320	415	390	15000	10000	855	200	1.0	1900
MYL2A32K561	560(504-616)	350	455	390	15000	10000	945	200	1.0	1700
MYL2A32K621	620(558-682)	380	505	390	15000	10000	1025	200	1.0	1500
MYL2A32K681	680(612-748)	420	560	400	15000	10000	1120	200	1.0	1300
MYL2A32K751	750(675-825)	460	615	440	15000	10000	1240	200	1.0	1250
MYL2A32K821	820(738-902)	510	670	500	15000	10000	1355	200	1.0	1200
MYL2A32K911	910(819-1001)	550	745	550	15000	10000	1500	200	1.0	1100
MYL2A32K102	1000(900-1100)	625	825	600	15000	10000	1650	200	1.0	1000
MYL2A32K112	1100(990-1210)	680	895	650	15000	10000	1815	200	1.0	900
MYL2A32K122	1200(1080-1320)	705	970	700	15000	10000	1980	200	1.0	800

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电 压		能量	最大峰值电流		最大峰值电压		静态功 率	电容量 (参考值)
	Vari toVoltage	Max. Allowable Voltage(V)		Energy (2ms)	Max. Peak Current (8/20, s) (A)		Max. Clamping Voltage		Rared Power	Capaci tance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	(J)	1time	2time	Vc(V)	I _p (A)	(W)	pF
MYL2A40K470	47(42-52)	30	38	70	10000	5000	93	100	0.3	30000
MYL2A40K560	56(50-62)	35	45	80	10000	5000	110	100	0.3	27000
MYL2A40K680	68(61-75)	40	56	90	10000	5000	115	100	0.3	25000
MYL2A40K820	82(74-90)	50	65	100	10000	5000	135	100	0.3	20000
MYL2A40K101	100(90-110)	60	85	110	10000	5000	165	100	0.3	18000
MYL2A40K121	120(108-130)	75	100	120	10000	5000	200	100	0.3	16000
MYL2A40K151	150(135-165)	95	125	130	10000	5000	250	100	1.2	13000
MYL2A40K181	180(162-198)	115	150	140	10000	5000	300	100	1.2	10000
MYL2A40K201	200(180-220)	130	170	270	30000	20000	340	250	1.2	6200
MYL2A40K221	220(198-242)	140	180	270	30000	20000	360	250	1.2	5500
MYL2A40K241	240(216-264)	150	200	300	30000	20000	395	250	1.2	5100
MYL2A40K271	270(243-297)	175	225	300	30000	20000	455	250	1.2	4800
MYL2A40K301	300(270-330)	190	245	330	30000	20000	495	250	1.2	4300
MYL2A40K331	330(297-363)	215	275	350	30000	20000	540	250	1.2	4000
MYL2A40K361	360(324-396)	230	300	350	30000	20000	595	250	1.2	3800
MYL2A40K391	390(351-429)	250	320	370	30000	20000	650	250	1.2	3400
MYL2A40K431	430(387-473)	275	350	400	30000	20000	710	250	1.2	3100
MYL2A40K471	470(423-517)	300	385	430	30000	20000	775	250	1.2	2800
MYL2A40K511	510(459-561)	320	415	460	30000	20000	855	250	1.2	2600
MYL2A40K561	560(504-616)	350	455	500	30000	20000	945	250	1.2	2400
MYL2A40K621	620(558-682)	380	505	550	30000	20000	1025	250	1.2	2100
MYL2A40K681	680(612-748)	420	560	600	30000	20000	1120	250	1.2	1900
MYL2A40K751	750(675-825)	460	615	650	30000	20000	1240	250	1.2	1700
MYL2A40K821	820(738-902)	510	670	700	30000	20000	1355	250	1.2	1600
MYL2A40K911	910(819-1001)	550	745	750	30000	20000	1500	250	1.2	1500
MYL2A40K102	1000(900-1100)	625	825	800	30000	20000	1650	250	1.2	1350
MYL2A40K112	1100(990-1210)	680	895	900	30000	20000	1815	250	1.2	1200
MYL2A40K122	1200(1080-1320)	705	970	1050	30000	20000	1980	250	1.2	1050